



# CYGNUS 40<sup>TH</sup> ANNIVERSARY



Standard probe supplied

	<b>S5A</b> Ideal for: Small diameter pipes and boiler tubes/heat exchangers	<b>S5C</b> Ideal for: Measuring wall thickness down to 1 mm (0.040 inch)	<b>S3C</b> Ideal for: Measuring wall thickness down to 2mm/0.080in with corrosion through coatings	<b>S2C</b> Ideal for: all round measurement of wall thickness with corrosion through coatings
Frequency	5 MHz	5 MHz	3.5 MHz	2.25 MHz
Tip Size	6mm (0.24 in)	13mm (0.5 in)	13mm (0.5 in)	13mm (0.5 in)
Range in Steel	1 - 50mm (0.040 - 2in)	1 - 50mm (0.040 - 2in)	2 - 150mm (0.080 - 6in)	3 - 250mm (0.120 - 10in)
Connectors	Lemo 00	BNC	BNC	BNC
Colour	Black Face	Black Band	Orange Band	Red Band

All probes need to be used with Ultrasonic Couplant when taking measurements (excl. underwater)



EQUIPAMENTOS PARA ENSAIOS E INSPEÇÃO

☎ (19) 99768.8232 🏠 [www.cmarques.com.br](http://www.cmarques.com.br)

✉ [cmarques@cmarques.com.br](mailto:cmarques@cmarques.com.br)